

- CARACTERISTIQUES DES COMMANDES DE COMPTEUR -

T Y P E	M A R Q U E	C O M M A N D E					C A B L E		
		N° P. D.	Long.	Carré Sup.	Ecrou Sup.	Ecrou Inf.	N° P. D.	Long. Totale	Carré Inf.
S.C.C.	E.D.	4 548	1,580	3	12x100	Tournevis			
D.45.S.	E.D.	6 191	1,540	3	12x100		6 269	1,588	2
Z.2.C.	E.D.	8 728	1,050	3	12x100	Tournevis			
Z.54.C.	E.D.	8 970	1,067	2,7	11x 75	Tournevis			
S.B.	E.D.	10 337	0,920	2	11x 75	Tournevis			
S.B.H. - S - M	E.D.	10 419	1,296	2,7	11x 75	Tournevis			
S.B.(transf. tablier)	E.D.	10 540	1,097	2	11x75	Tournevis			
L.4.C.	O.S.	12 495	1,045	3	12x100	Tournevis			
AV.37	E.D.	14 817	0,605	2	11x 75		14 834	0,639	2
75 - 78 - 85 - 88	HURET	15 370	0,550	2,5	11x100	11x100	15 371	0,576	2,5
75 - 78 - 85 - 88	E.D.	15 574	0,571	2	11x 75		15 575	0,605	2
AV.87 1er Mle	E.D.	15 858	0,810	2	11x 75		15 859	0,846	2
AV.87 2ème Mle	E.D.	16 695	0,803	2	11x 75		15 859	0,846	2